

Page 1 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

THT-DIESEL-SPEC.OIL 15W40 5 L

Art.: 1073

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Motor oil

(GB)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet $\overline{}^{\scriptscriptstyle(\ensuremath{\mathbb{R}})}$

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains Calcium alkyl aryl sulfonate, long chain. May produce an allergic reaction. EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

May produce an allergic reaction.

Hazardous to drinking water, on escape of even small quantities.

Product can compose a film on the water surface, which can prevent oxygen exchange.



Page 2 of 10

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3 2 Mixture

| Polyolefin polyamine succinimide, Polyol | |
|---|-------------------------|
| Registration number (REACH) | |
| Index | |
| EINECS, ELINCS, NLP | 604-611-9 |
| CAS | 147880-09-9 |
| content % | 1-<5 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Aquatic Chronic 4, H413 |
| | |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary. Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration

4.2 Most important symptoms and effects, both acute and delayed

with long-term contact: Drying of the skin. Irritation of the skin. Sensitive individuals: Allergic reaction possible.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. 4.3 Indication of any immediate medical attention and special treatment needed n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media CO2 Foam Dry extinguisher Water jet spray Unsuitable extinguishing media High volume water jet



Page 3 of 10

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Fume Oxides of carbon Oxides of nitrogen Hydrogen sulphide Aldehydes Toxic pyrolysis products. Flammable vapour/air mixtures

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist. Remove possible causes of ignition - do not smoke. Avoid inhalation, and contact with eyes or skin. If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not heat to temperatures close to flash point.

Take measures against electrostatic charging, if appropriate.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with flammable or self-igniting materials.

Impermeable floor.



Page 4 of 10

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Oil mist, mineral | Content %: |
|--------------------------|--------------------------------------|------------|
| WEL-TWA: 5 mg/m3 (ACGIH) | WEL-STEL: 10 mg/m3 (ACGIH) | - |
| Monitoring procedures: | - Draeger - Oil 10/a-P (67 28 371) | |
| | - Draeger - Oil Mist 1/a (67 33 031) | |
| BMGV: | Other information: | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Protective gloves, oil resistant (EN 374) If applicable Protective nitrile gloves (EN 374) Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: > 480 Protective gloves made of polyvinyl alcohol (EN 374) Protective gloves made of polyvinyl alcohol (EN 374) Protective Viton® / fluoroelastomer gloves (EN 374) Protective hand cream recommended. The recommended maximum wearing time is 50% of breakthrough time. The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions. Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. With oil mist formation:



Page 5 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

Filter A2 P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

(GB)

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | vents content: | Not determined |
|---------------------|---------------------------------------|---|
| | | Not determined |
| Surf | face tension: | Not determined |
| | ductivity: | Not determined |
| | solubility / solvent: | Not determined |
| | cibility: | Not determined |
| | | |
| | Other information | |
| | dising properties: | Not determined |
| | losive properties: | Not determined |
| | cosity: | 14,2-14,4 mm2/s (100°C) |
| | cosity: | 100-108 mm2/s (40°C) |
| | composition temperature: | Not determined |
| | p-ignition temperature: | Not determined |
| | tition coefficient (n-octanol/water): | Not determined |
| | ter solubility: | Insoluble |
| | ubility(ies): | Not determined |
| | density: | Not determined |
| Den | , , | 0,88-0,888 g/ml |
| | our density (air = 1): | Not determined |
| | our pressure: | Not determined |
| | er explosive limit: | Not determined |
| | ver explosive limit: | Not determined |
| | nmability (solid, gas): | Not determined |
| | poration rate: | Not determined |
| | sh point: | 210-230 °C |
| | al boiling point and boiling range: | Not determined |
| | ting point/freezing point: | Not determined |
| | value: | Not determined |
| | | |
| | | |
| | | • |
| | | · · |
| Phys Colo Odo | | Liquid Brown Characteristic Not determined |

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6. The product has not been tested. **10.2 Chemical stability**

See also Subsection 10.1 to 10.6. Stable with proper storage and handling.



Page 6 of 10

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6. No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7. Protect from humidity. Open flame, ignition sources **10.5 Incompatible materials**

See also section 7. Avoid contact with strong oxidizing agents. Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5. See also section 5.2 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

| Possibly more information on heal THT-DIESEL-SPEC.OIL 15W40 5 | / | e Section 2.1 (| classification). | | | |
|--|----------|-----------------|------------------|----------|-------------|--------|
| Art.: 1073 | | | | | | |
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | • | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - | | | | | | n.d.a. |
| single exposure (STOT-SE): | | | | | | |
| Specific target organ toxicity - | | | | | | n.d.a. |
| repeated exposure (STOT-RE): | | | | | | |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

SECTION 12: Ecological information

| Possibly more information on environmental effects, see Section 2.1 (classification). | | | | | | | |
|---|----------|------|-------|------|----------|-------------|------------------|
| THT-DIESEL-SPEC.OIL 15W40 5 L | | | | | | | |
| Art.: 1073 | | | | | | | |
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and | | | | | | | (Particulars of |
| degradability: | | | | | | | main substances |
| | | | | | | | contained) Not |
| | | | | | | | readily but |
| | | | | | | | inherent |
| | | | | | | | biodegradable. |
| 12.3. Bioaccumulative | | | | | | | Concentration in |
| potential: | | | | | | | organisms |
| | | | | | | | possible. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |



Page 7 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

| 12.5. Results of PBT | | | | n.d.a. |
|----------------------|--|--|--|--------|
| and vPvB assessment | | | | |
| 12.6. Other adverse | | | | n.d.a. |
| effects: | | | | |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

EC disposal code no.:

(GB)

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

| General statements | | |
|---|------------------|--|
| 14.1. UN number: | n.a. | |
| Transport by road/by rail (ADR/RID) | | |
| 14.2. UN proper shipping name: | | |
| 14.3. Transport hazard class(es): | n.a. | |
| 14.4. Packing group: | n.a. | |
| Classification code: | n.a. | |
| LQ (ADR 2015): | n.a. | |
| 14.5. Environmental hazards: | Not applicable | |
| Tunnel restriction code: | | |
| Transport by sea (IMDG-code) | | |
| 14.2. UN proper shipping name: | | |
| 14.3. Transport hazard class(es): | n.a. | |
| 14.4. Packing group: | n.a. | |
| Marine Pollutant: | n.a | |
| 14.5. Environmental hazards: | Not applicable | |
| Transport by air (IATA) | | |
| 14.2. UN proper shipping name: | | |
| 14.3. Transport hazard class(es): | n.a. | |
| 14.4. Packing group: | n.a. | |
| 14.5. Environmental hazards: | Not applicable | |
| 14.6. Special precautions for user | | |
| Unless specified otherwise, general measures for safe transport m | ust be followed. | |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information



Page 8 of 10

GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 % National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

3

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H413 May cause long lasting harmful effects to aquatic life.

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

Article Categories AC according, according to acc., acc. to ACGIH American Conference of Governmental Industrial Hygienists ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF Bioconcentration factor BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight CAS **Chemical Abstracts Service** CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques CIPAC Collaborative International Pesticides Analytical Council CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level



(GB) Page 9 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073 DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) DVS dw drv weight e.g. EC for example (abbreviation of Latin 'exempli gratia'), for instance European Community ECHA European Chemicals Agency EEA European Economic Area European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances ELINCS European List of Notified Chemical Substances ΕN European Norms EPA United States Environmental Protection Agency (United States of America) ERC **Environmental Release Categories** ES Exposure scenario etc. et cetera European Union FU EWC European Waste Catalogue Fax. Fax number gen. deneral GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential International Agency for Research on Cancer IARC IATA International Air Transport Association IBC Intermediate Bulk Container IBC (Code) International Bulk Chemical (Code) Inhibitory concentration IC IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLID International Uniform ChemicaL Information Database lethal concentration LC LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration LD Lethal Dose of a chemical LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. no data available n.d.a. NIOSH National Institute of Occupational Safety and Health (United States of America) NOAEC No Observed Adverse Effective Concentration NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level **Ozone Depletion Potential** ODP OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic PC Chemical product category Polyethylene PE PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential parts per million ppm PROC Process category PTFE Polytetrafluorethylene



Page 10 of 10 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 22.11.2016 / 0014 Replacing version dated / version: 21.08.2015 / 0013 Valid from: 22.11.2016 PDF print date: 22.11.2016 THT-DIESEL-SPEC.OIL 15W40 5 L Art.: 1073

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List **REACH-IT List-No.** Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship Sector of use SU SVHC Substances of Very High Concern Telephone Tel. ThOD Theoretical oxygen demand тос Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

(GB)

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.